

# RIDE ON ROLLER



## Technical Parameters

MODEL	UNI 880	UNI 1200
WEIGHT	800 KGS	1000 KGS
CAPACITY OF WATER TANK	35 LTR.	60 LTR.
CAPACITY OF OIL TANK	3.6 LTR.	19 LTR.
WALKING SPEED	0-4 KM/H	0-5 KM/H
TURNING RADIUS	2000MM	2500MM
STARTING WAY	ELECTRICAL STARTING	ELECTRICAL STARTING
DRIVE MODEL	MECHANICAL	HYDRAULIC
WALKING MODEL	FORWARDING & BACK	FORWARDING & BACK
WHEEL SIZE	750 Ø 560MM (FORWARD) 500 560MM (BACK)	800 560MM (FORWARD) 800*560MM (BACK)
VIBRATING CLUTCH METHOD	ELECTROMAGNETIC	ELECTROMAGNETIC
CENTRIFUGAL FORCE	35 KN (3.5 TON)	50 KN (5 TON)
VIBRATION FREQUENCY	70 HZ	70 HZ
GRADE ABILITY	30%	30%
PACKAGE SIZE	2000*900*1400MM	1900*920*1500MM
ENGINE	DIESEL / PETROL ENGINE	IMPORTED DIESEL ENGINE
ENGINE TYPE	GREAVES AIR COOL DIESEL	AIR COOL DIESEL
FUEL CONSUMPTION	200G/KWH	280G/KWH
COMPACTION AREA	40000 SQ FT P/H	50000 SQ FT P/H

**NASHIK**